

Universal Light Duty Cartridge Vessel LCF Series

Versatile design for general purpose application cartridge vessel, available in 3 , 5 and 7 rounds in SS304 and SS316 material. We are able to supply for all industrial standard DOE and SOE configuration of up to 50” length cartridge.



Feature –

Convenient V Clamp closure design for easy cartridge change out

Unique design able to fit either DOE (double open end) or SOE with “222” configuration.

Other SOE configurations ‘226’ also available

SS304 and SS316 material construction are our standard.

Smooth Bead blasted finishing for easy cleaning, electro-polishing is optional

Max Operating pressure – 10 Bar at 25 Deg C

Inlet/Outlet Connection - 1 ½” NPT or 2” - 3” ANSI Flange

Vent/Drain - ¼” / ¾” NPT

O Ring – EPDM, Viton or Telfon encapsulated Viton

Connection Option - DIN, JIS10K Flange, BSP coupling or others.

Manufacturer - Universal Filtration Solutions Asia Pte Ltd

Eunos Warehouse Complex, 1 Kaki Bukit Road 2 #02-08
Singapore 417835

Tel + 65 68417629 Fax +65 6841 7091

www.universal-filtration.com

sales-inquiry@universal-filtration.com

Cartridge Filter

Ordering Information –

LCF 520	CS	-10-	020A
# of rounds - 3,5,7,9	A - SS304 S - SS316 SL - SS316L	6 Bar 10 Bar	A - ANSI Flange J - JIS Flange D - DIN Flange N - NSP B - BSP
Length Of cartridge 10", 20", 30" 40" , 50"			Flange Size 2", 3"

**Manufacturer -
Universal Filtration Solutions Asia Pte Ltd**

Eunos Warehouse Complex, 1 Kaki Bukit Road 2 #02-08
Singapore 417835

Tel + 65 68417629 Fax +65 6841 7091
sales-inquiry@universal-filtration.com

www.universal-filtration.com